



Thermory's thermally stabilised timbers offer a range of natural or pre-finished, ready to install, cladding and lining solutions. Featuring spruce and pine ranges that are responsibly sourced from sustainably grown plantation timbers. These timbers are thermally modified using heat and steam, to produce a durable, high performing product range that carries a Class 1 durability rating to perform for decades in Australian conditions.

Thermory modifies the timber for increased durability and dimensional stability in a range of natural and prefinished, ready to install exterior cladding and interior lining solutions.

## Spruce Cladding Intense: Drift Sandy Pearl C15



Sustainable Thermory® cladding and lining in a Drift finish and Brushed texture offers the rustic look of reclaimed timber. This spruce cladding is FSC certified and responsibly sourced from plantation timbers. Ideal for a coastal aesthetic, this blonde timber features a lime wash and delivers the performance of a thermally modified timber product, offering durability and dimensional stability.

**Texture**  
Brushed


**Grade**  
Class 1 Durability  
Thermally Stabilised Timber

**Colour**  
Sandy tones and lime wash

**Species**  
Spruce


**Size (mm)**  
186 x 20

### C15 Profile:



C24: 186 x 20 / cover: 175mm

### Corner thermo - spruce CP3



One universal profile for indoor and outdoor usage. Boards with straight-cut ends can be installed without exposing the endgrain.

42x42



CLASS 1



**Durability**  
Improved Durability and rot resistance



**Stability**  
Enhanced dimensional stability in changing weather conditions



**Chemical-Free**  
Thermal modification process is entirely natural

Call 1300 399 922  
or email [info@citytimber.com.au](mailto:info@citytimber.com.au)  
1400 Centre Rd, Clayton South 3169  
[citytimber.com.au](http://citytimber.com.au)

