

# Supared LVL E14 H2S Laminated Veneer Lumber



## Strength & Versatility:

**SUPARED LVL** highly versatile laminated veneer lumber (LVL) with superior structural performance than lower-grade LVL or traditional sawn timber. Its enhanced strength and stiffness spans longer distances, ideal for demanding structural use delivering reliability you need for long-lasting construction.

**SUPARED LVL** ideal for key structural elements such as:

- Outdoor patios
- Decks
- Lintels
- Beams
- Rafters
- Floor joists

## Water Repellence:

**SUPARED LVL** H2 treatment offers short-term water repellence with a high-penetration, water-based surface protection built to repel rain during storage and construction. It is compatible with both oil-based and acrylic paints and it can be glued using standard construction-approved adhesives.

## Range:

**SUPARED LVL** in sizes:  
Thicknesses: 35, 45 and 63mm  
Widths: 90, 120, 140, 190, 240, 290, 300, 360 and 400mm

## Performance:

**SUPARED LVL** strong, mass-produced wood designed for the Australian market. It is a direct substitute for F17 hardwoods. Manufactured in accordance with AS/NZS 4357 and is the standard for structural laminated veneer lumber.

## Treatment:

**SUPARED LVL** LVL products come standard with H2S treatment, providing protection against termite attack in areas south of the Tropic of Capricorn. For regions north of the Tropic of Capricorn, post-production H2 termite treatment available upon request. H3 treatment for external use offered on request.

## Sustainability:

**SUPARED LVL** is DNA-tested to thoroughly verify that it is legally sourced, sustainably harvested and fully PEFC compliant with regulatory standards.

Refer to nail plate manufacturer PRYDA

